**TCB** 

## GRANT OF EQUIPMENT AUTHORIZATION

**TCB** 

## Certification

Issued Under the Authority of the Federal Communications Commission

By:

Bay Area Compliance Laboratory Corp. 1274 Anvilwood Avenue Sunnyvale, CA 94089

Date of Grant: 08/21/2015

Application Dated: 08/21/2015

## SHENZHEN COVALUE COMMUNICATIONS CO., LTD.

2/F., Bldg. 24, XiLi Industrial Park, No.119 Xinguang Rd, Xili, Nanshan Shenzhen, 518055 China

Attention: Chengtao Shu, Engineer

## **NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: Y4GDM6000-1

Name of Grantee: SHENZHEN COVALUE

COMMUNICATIONS CO., LTD.

**Equipment Class: Licensed Non-Broadcast Station** 

Transmitter

Notes: Mobile Radio

Grant Notes	FCC Rule Parts	Frequency Range (MHZ)	Output <u>Watts</u>	Frequency Tolerance	Emission Designator
EF ES	22, 90	136.0 - 174.0	50.0	0.22 PM	10K3F3E
EF ES	22, 90	136.0 - 174.0	50.0	0.22 PM	8K92FXD
EF ES	22, 90	136.0 - 174.0	50.0	0.22 PM	8K92FXW
EF ES	22, 90	136.0 - 174.0	25.0	0.22 PM	10K4F3E
EF ES	22, 90	136.0 - 174.0	25.0	0.22 PM	8K69FXD
EF ES	22, 90	136.0 - 174.0	25.0	0.22 PM	8K69FXW

Output power listed is rated conducted. This transmitter must be restricted to work related operations in an Occupational/Controlled RF exposure environment, not exceeding a maximum transmitting duty factor of 50%. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 0.8 m from all persons. Users must be provided with the training information, antenna installation and transmitter operating conditions for satisfying RF exposure compliance.

EF: This device may contain functions that are not operational in U.S Territories except as noted in the filing. This grant has extended frequencies as noted in the filing and Section 2.927(b) applies to this authorization.

ES: This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth.