

TCB**GRANT OF EQUIPMENT
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the
Federal Communications Commission****By:****Bay Area Compliance Laboratory
Corp.
1274 Anvilwood Avenue
Sunnyvale, CA 94089****Date of Grant: 07/31/2014****Application Dated: 07/31/2014****SHENZHEN COVALUE COMMUNICATIONS CO., LTD.****2/F., Bldg. 24, XiLi Industrial Park, No.119****Xinguang Rd, Xili, Nanshan****Shenzhen, 518055****China****Attention: Chengtao Shu , Engineer****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: Y4GDR6000-1
Name of Grantee: SHENZHEN COVALUE COMMUNICATIONS CO., LTD.
Equipment Class: Licensed Non-Broadcast Transmitter Held to Face
Notes: Two Way Radio

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
BE EF	90	136.0 - 174.0	5.27	0.4 PM	11K0F3E
BE EF	90	136.0 - 174.0	5.27	0.4 PM	7K60FXD
BE EF	90	136.0 - 174.0	5.27	0.4 PM	7K60FXW

Power output listed is conducted. This device must be restricted to work-related operations only in an Occupational/Controlled RF exposure environment and must operate with a duty factor not exceeding 50%. This transmitter may operate with the antenna(s) documented in this filing in Push-to-Talk and body-worn configurations. RF exposure compliance is limited to the specific belt-clip and accessory configurations as documented in this filing and the separation distance between user and the device or its antenna shall be at least 2.5 cm. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with Occupational/Controlled Exposure limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements. The highest reported SAR values for Face held and Body-worn accessory are 0.22 W/Kg and 1.52 W/Kg respectively.

BE: The output power is continuously variable from the value listed in this entry to 15%-20% of the value listed.

EF: This device may contain functions that are not operational in U.S Territories except as noted in the filing. This grant has extended frequencies as noted in the filing and Section 2.927(b) applies to this authorization.